

Lin Li · Bora Cetin · Xiaoming Yang  
*Editors*

Proceedings of  
GeoShanghai 2018  
International Conference:  
Ground Improvement  
and Geosynthetics

 Springer

Proceedings of GeoShanghai 2018 International  
Conference: Ground Improvement  
and Geosynthetics

Lin Li · Bora Cetin · Xiaoming Yang  
Editors

Proceedings of GeoShanghai  
2018 International  
Conference: Ground  
Improvement  
and Geosynthetics

 Springer

*Editors*

Lin Li  
Department of Civil  
and Environmental Engineering  
Jackson State University  
Jackson, MS  
USA

Xiaoming Yang  
Oklahoma State University  
Oklahoma, OK  
USA

Bora Cetin  
Iowa State University  
Ames, IA  
USA

ISBN 978-981-13-0121-6      ISBN 978-981-13-0122-3 (eBook)  
<https://doi.org/10.1007/978-981-13-0122-3>

Library of Congress Control Number: 2018939621

© Springer Nature Singapore Pte Ltd. 2018

This work is subject to copyright. All rights are reserved by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed.

The use of general descriptive names, registered names, trademarks, service marks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

The publisher, the authors and the editors are safe to assume that the advice and information in this book are believed to be true and accurate at the date of publication. Neither the publisher nor the authors or the editors give a warranty, express or implied, with respect to the material contained herein or for any errors or omissions that may have been made. The publisher remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Printed on acid-free paper

This Springer imprint is published by the registered company Springer Nature Singapore Pte Ltd. part of Springer Nature  
The registered company address is: 152 Beach Road, #21-01/04 Gateway East, Singapore 189721, Singapore

# Preface

The 4th GeoShanghai International Conference was held on May 27–30, 2018, in Shanghai, China. GeoShanghai is a series of international conferences on geotechnical engineering held in Shanghai every four years. The conference was inaugurated in 2006 and was successfully held in 2010 and 2014, with more than 1200 participants in total. The conference offers a platform of sharing recent developments of the state-of-the-art and state-of-the-practice in geotechnical and geoenvironmental engineering. It has been organized by Tongji University in cooperation with the ASCE Geo-Institute, Transportation Research Board, and other cooperating organizations.

The proceedings of the 4th GeoShanghai International Conference include eight volumes of over 560 papers; all were peer-reviewed by at least two reviewers. The proceedings include Volumes 1: Fundamentals of Soil Behavior edited by Dr. Annan Zhou, Dr. Junliang Tao, Dr. Xiaoqiang Gu, and Dr. Liangbo Hu; Volume 2: Multi-physics Processes in Soil Mechanics and Advances in Geotechnical Testing edited by Dr. Liangbo Hu, Dr. Xiaoqiang Gu, Dr. Junliang Tao, and Dr. Annan Zhou; Volume 3: Rock Mechanics and Rock Engineering edited by Dr. Lianyang Zhang, Dr. Bruno Goncalves da Silva, and Dr. Cheng Zhao; Volume 4: Transportation Geotechnics and Pavement Engineering edited by Dr. Xianming Shi, Dr. Zhen Liu, and Dr. Jenny Liu; Volume 5: Tunneling and Underground Construction edited by Dr. Dongmei Zhang and Dr. Xin Huang; Volume 6: Advances in Soil Dynamics and Foundation Engineering edited by Dr. Tong Qiu, Dr. Binod Tiwari, and Dr. Zhen Zhang; Volume 7: Geoenvironment and Geohazards edited by Dr. Arvin Farid and Dr. Hongxin Chen; and Volume 8: Ground Improvement and Geosynthetics edited by Dr. Lin Li, Dr. Bora Cetin, and Dr. Xiaoming Yang. The proceedings also include six keynote papers presented at the conference, including “Tensile Strains in Geomembrane Landfill Liners” by Prof. Kerry Rowe, “Constitutive Modeling of the Cyclic Loading Response of Low Plasticity Fine-Grained Soils” by Prof. Ross Boulanger, “Induced Seismicity and Permeability Evolution in Gas Shales, CO<sub>2</sub> Storage and Deep Geothermal Energy” by Prof. Derek Elsworth, “Effects of Tunneling on Underground Infrastructures” by Prof. Maosong Huang, “Geotechnical Data Visualization and Modeling of Civil

Infrastructure Projects” by Prof. Anand Puppala, and “Probabilistic Assessment and Mapping of Liquefaction Hazard: from Site-specific Analysis to Regional Mapping” by Prof. Hsein Juang. The Technical Committee Chairs, Prof. Wenqi Ding and Prof. Xiong Zhang, the Conference General Secretary, Dr. Xiaoqiang Gu, the 20 editors of the 8 volumes and 422 reviewers, and all the authors contributed to the value and quality of the publications.

The Conference Organizing Committee thanks the members of the host organizations, Tongji University, Chinese Institution of Soil Mechanics and Geotechnical Engineering, and Shanghai Society of Civil Engineering, for their hard work and the members of International Advisory Committee, Conference Steering Committee, Technical Committee, Organizing Committee, and Local Organizing Committee for their strong support. We hope the proceedings will be valuable references to the geotechnical engineering community.

Shijin Feng  
Conference Chair  
Ming Xiao  
Conference Co-chair

# Organization

## International Advisory Committee

Herve di Benedetto	University of Lyon, France
Antonio Bobet	Purdue University, USA
Jean-Louis Briaud	Texas A&M University, USA
Patrick Fox	Penn State University, USA
Edward Kavazanjian	Arizona State University, USA
Dov Leshchinsky	University of Illinois, USA
Wenhao Liang	China Railway Construction Corporation Limited, China
Robert L. Lytton	Texas A&M University, USA
Louay Mohammad	Louisiana State University, USA
Manfred Partle	KTH Royal Institute of Technology, Switzerland
Anand Puppala	University of Texas at Arlington, USA
Mark Randolph	University of Western Australia, Australia
Kenneth H. Stokoe	University of Texas at Austin, USA
Gioacchino (Cino) Viggiani	Université Joseph Fourier, France
Dennis T. Bergado	Asian Institute of Technology, Thailand
Malcolm Bolton	Cambridge University, UK
Yunmin Chen	Zhejiang University, China
Zuyu Chen	Tsinghua University, China
Jincai Gu	PLA, China
Yaoru Lu	Tongji University, China
Herbert Mang	Vienna University of Technology, Austria
Paul Mayne	Georgia Institute of Technology, USA
Stan Pietruszczak	McMaster University, Canada
Tom Papagiannakis	Washington State University, USA
Jun Sun	Tongji University, China

Scott Sloan	University of Newcastle, Australia
Hywel R. Thomas	Cardiff University, UK
Atsashi Yashima	Gifu University, Japan

## Conference Steering Committee

Jie Han	University of Kansas, USA
Baoshan Huang	University of Tennessee, USA
Maosong Huang	Tongji University, China
Yongsheng Li	Tongji University, China
Linbin Wang	Virginia Tech, USA
Lianyang Zhang	University of Arizona, USA
Hehua Zhu	Tongji University, China

## Technical Committee

Wenqi Ding (Chair)	Tongji University, China
Charles Aubeny	Texas A&M University, USA
Rifat Bulut	Oklahoma State University, USA
Geoff Chao	Asian Institute of Technology, Thailand
Jian Chu	Nanyang Technological University, Singapore
Eric Drumm	University of Tennessee, USA
Wen Deng	Missouri University of Science and Technology, USA
Arvin Farid	Boise State University, Idaho, USA
Xiaoming Huang	Southeast University, China
Woody Ju	University of California, Los Angeles, USA
Ben Leshchinsky	Oregon State University, Oregon, USA
Robert Liang	University of Dayton, Ohio, USA
Hoe I. Ling	Columbia University, USA
Guowei Ma	Hebei University of Technology, China
Roger W. Meier	University of Memphis, USA
Catherine O'Sullivan	Imperial College London, UK
Massimo Losa	University of Pisa, Italy
Angel Palomino	University of Tennessee, USA
Krishna Reddy	University of Illinois at Chicago, USA
Zhenyu Yin	Tongji University, China
Zhongqi Yue	University of Hong Kong, China
Jianfu Shao	Université des Sciences et Technologies de Lille 1, France
Jonathan Stewart	University of California, Los Angeles, USA



Wei Wu	University of Natural Resources and Life Sciences, Austria
Jianhua Yin	The Hong Kong Polytechnic University, China
Guoping Zhang	University of Massachusetts, USA
Jianmin Zhang	Tsinghua University, China
Xiong Zhang (Co-chair)	Missouri University of Science and Technology, USA
Yun Bai	Tongji University, China
Jinchun Chai	Saga University, Japan
Cheng Chen	San Francisco State University, USA
Shengli Chen	Louisiana State University, USA
Yujun Cui	École Nationale des Ponts et Chaussées (ENPC), France
Mohammed Gabr	North Carolina State University, USA
Haiying Huang	Georgia Institute of Technology, USA
Laureano R. Hoyos	University of Texas at Arlington, USA
Liangbo Hu	University of Toledo, USA
Yang Hong	University of Oklahoma, USA
Minjing Jiang	Tongji University, China
Richard Kim	North Carolina State University, USA
Juanyu Liu	University of Alaska Fairbanks, USA
Matthew Mauldon	Virginia Tech., USA
Jianming Ling	Tongji University, China
Jorge Prozzi	University of Texas at Austin, USA
Daichao Sheng	University of Newcastle, Australia
Joseph Wartman	University of Washington, USA
Zhong Wu	Louisiana State University, USA
Dimitrios Zekkos	University of Michigan, USA
Feng Zhang	Nagoya Institute of Technology, Japan
Limin Zhang	Hong Kong University of Science and Technology, China
Zhongjie Zhang	Louisiana State University, USA
Annan Zhou	RMIT University, Australia
Fengshou Zhang	Tongji University, China

## Organizing Committee

Shijin Feng (Chair)	Tongji University, China
Xiaoqiang Gu (Secretary General)	Tongji University, China
Wenqi Ding	Tongji University, China
Xiongyao Xie	Tongji University, China

Yujun Cui	École Nationale des Ponts et Chaussées (ENPC), France
Daichao Sheng	University of Newcastle, Australia
Kenichi Soga	University of California, Berkeley, USA
Weidong Wang	Shanghai Xian Dai Architectural Design (Group) Co., Ltd., China
Feng Zhang	Nagoya Institute of Technology, Japan
Yong Yuan	Tongji University, China
Weimin Ye	Tongji University, China
Ming Xiao (Co-chair)	Penn State University, USA
Yu Huang	Tongji University, China
Xiaojun Li	Tongji University, China
Xiong Zhang	Missouri University of Science and Technology, USA
Guenther Meschke	Ruhr-Universität Bochum, Germany
Erol Tutumluer	University of Illinois, Urbana—Champaign, USA
Jianming Zhang	Tsinghua University, China
Jianming Ling	Tongji University, China
Guowei Ma	Hebei University of Technology, Australia
Hongwei Huang	Tongji University, China

## Local Organizing Committee

Shijin Feng (Chair)	Tongji University, China
Zixin Zhang	Tongji University, China
Jiangu Qian	Tongji University, China
Jianfeng Chen	Tongji University, China
Bao Chen	Tongji University, China
Yongchang Cai	Tongji University, China
Qianwei Xu	Tongji University, China
Qingzhao Zhang	Tongji University, China
Zhongyin Guo	Tongji University, China
Xin Huang	Tongji University, China
Fang Liu	Tongji University, China
Xiaoying Zhuang	Tongji University, China
Zhenming Shi	Tongji University, China
Zhiguo Yan	Tongji University, China
Dongming Zhang	Tongji University, China
Jie Zhang	Tongji University, China
Zhiyan Zhou	Tongji University, China
Xiaoqiang Gu (Secretary)	Tongji University, China
Lin Cong	Tongji University, China
Hongduo Zhao	Tongji University, China

Fayun Liang	Tongji University, China
Bin Ye	Tongji University, China
Zhen Zhang	Tongji University, China
Yong Tan	Tongji University, China
Liping Xu	Tongji University, China
Mengxi Zhang	Tongji University, China
Haitao Yu	Tongji University, China
Xian Liu	Tongji University, China
Shuilong Shen	Tongji University, China
Dongmei Zhang	Tongji University, China
Cheng Zhao	Tongji University, China
Hongxin Chen	Tongji University, China
Xilin Lu	Tongji University, China
Jie Zhou	Tongji University, China

# Contents

<b>Tensile Strains in Geomembrane Landfill Liners</b> . . . . .	1
R. Kerry Rowe and Yan Yu	
<b>Ground Improvement</b>	
<b>Application of Image Analysis on Two-Dimensional Experiment of Ground Displacement Under Strip Footing</b> . . . . .	13
Guanxi Yan, Youwei Xu, Vignesh Murgana, and Alexander Scheuermann	
<b>Calculation Method for Settlement of Stiffened Deep Mixed Column-Supported Embankment over Soft Clay</b> . . . . .	22
Guan-Bao Ye, Feng-Rui Rao, Zhen Zhang, and Meng Wang	
<b>Consolidation Analysis of Soft Soil by Vacuum Preloading Considering Groundwater Table Change</b> . . . . .	30
Yan Xu, Guan-Bao Ye, and Zhen Zhang	
<b>DEM Analysis of the Effect of Grain Size Distribution on Vibroflotation Without Backfill</b> . . . . .	41
Mingjing Jiang, Huali Jiang, and Banglu Xi	
<b>Steel Drilled Displacement Piles (M-Piles) – Overview and Case History</b> . . . . .	48
Antonio Marinucci and Stephen E. Wilson	
<b>Field Investigation of Highway Subgrade Silty Soil Treated with Lignin</b> . . . . .	59
Tao Zhang, Songyu Liu, Guojun Cai, and Longcheng Duan	
<b>Investigation of Ground Displacement Induced by Hydraulic Jetting Using Smoothed Particle Hydrodynamics</b> . . . . .	68
Pierre Guy Atangana Njock and Shuilong Shen	

<b>Monte-Carlo Simulation of Post-construction Settlement After Vacuum Consolidation and Design Criterion Calibration . . . . .</b>	76
Wei He, Mathew Sams, Barry Kok, and Pak Rega	
<b>Numerical Investigation on Slope Stability of Deep Mixed Column-Supported Embankments Over Soft Clay Induced by Strength Reduction and Load Increase . . . . .</b>	89
Zhen Zhang, Yan Xiao, Guan-Bao Ye, Jie Han, and Meng Wang	
<b>Performance of Clay Bed with Natural and Lightweight Aggregate Stone Columns . . . . .</b>	97
Trudeep N. Dave and Veerabhadrapa M. Rotte	
<b>Permeability Comparison of MgO-carboanted Soils and Cement-Treated Soils . . . . .</b>	105
Guang-Hua Cai, Song-Yu Liu, Guang-Yin Du, Liang Wang, and Chuan Qin	
<b>Resilient Modulus of Liquid Chemical-Treated Expansive Soils . . . . .</b>	114
Shi He, Xinbao Yu, Sandesh Gautam, Anand J. Puppala, and Ujwalkumar D. Patil	
<b>Stabilization of Marine Soft Clay with Two Industry By-products . . . . .</b>	121
Yaolin Yi and Pengpeng Ni	
<b>Study on Strength and Microscopic Properties of Stabilized Silt . . . . .</b>	129
Xiaobin Zhang, Zhiduo Zhu, and Renjie Wei	
<b>Stabilisation of Expansive Soil Against Alternate Wetting–Drying . . . . .</b>	137
An Deng	
<b>Application of Cone Penetration Test Technology in Whole Process Inspection of Reinforcing Hydraulic Fill Sand Foundation . . . . .</b>	145
De-yong Wang, Sheng Chen, Xiao-cong Liang, and Hong-xing Zhou	
<b>Curing of Sand Stabilized with Alkali Lignin . . . . .</b>	157
Qingwen Yang, Chao Zheng, and Jie Huang	
<b>Combined Encased Stone Column and Vacuum Consolidation Technique for Soft Clay Improvement . . . . .</b>	169
Ganesh Kumar	
<b>Numerical Simulation of Bearing Capacity and Consolidation Characteristics of PHC Pile Foundation . . . . .</b>	178
Shen Gong, Guojun Cai, Songyu Liu, and Anand J. Puppala	
<b>Experimental Study on Electro-Osmosis Consolidation with Solar Power for Silt . . . . .</b>	186
Huiming Tan, Jianjun Huang, and Jiawei Wang	

**Experimental Investigation on Compressive Deformation and Shear Strength Characteristics of Steel Slag in the Geotechnical Engineering** . . . . . 194  
 Li-yan Wang, Qi Wang, Xiang Huang, and Jia-tao Yan

**Predicting Compression Index Using Artificial Neural Networks: A Case Study from Dalian Artificial Island** . . . . . 203  
 Zhijia Xue, Xiaowei Tang, and Qing Yang

**Scale Influence of Treated Zone Under Vacuum Preloading** . . . . . 212  
 Liwen Hu, Fuling Yang, and Zhan Wang

**Research on Laboratory Mixing Trial of Marine Deposit and Cement in Hongkong** . . . . . 221  
 Yingxi He, Heping Yang, Jiayong Yang, Haipeng Liu, and Pengcheng Zhao

**Experimental Investigation of Black Cotton Soil Stabilized with Lime and Coconut Coir** . . . . . 230  
 A. U. Ravi Shankar, B. J. Panditharadhya, Satish Karishekki, and S. Amulya

**Influence of Damping Forms on the Behavior of Sand Under Dynamic Compaction** . . . . . 244  
 Yuqi Li, Jun Chen, and Jiejun Zhu

**Numerical Investigation on the Effect of Saturated Silty Soils Under Multi-location Tamping** . . . . . 252  
 Wei Wang, Jianhua Wang, and Qingsong Feng

**A Numerical Back Analysis of a Ground Improvement Project on Underconsolidated Clay Under Combined Vacuum and Surcharge Preloading in Macau** . . . . . 260  
 Yue Chen, Thomas Man Hoi Lok, and Hei Yip Lee

**Geosynthetics**

**Application of Large-Size Sandbag Cofferdam in Land Reclamation Engineering** . . . . . 271  
 Weiping Peng, Lingwei Chen, and Xiaowen Zhou

**Centrifuge Model Tests of Basal Reinforcement Effects on Geosynthetic-Reinforced Pile-Supported Embankment** . . . . . 279  
 Chao Xu, Di Wu, Shitong Song, and Baochen Liu

**Comparison Test of Different Drainage in Single Well Model for Vacuum Preloading** . . . . . 288  
 Jing Wang and Yongping Wang

<b>Design Charts for Reinforced Slopes with Turning Corner</b> . . . . .	297
Fei Zhang, Dov Leshchinsky, Yufeng Gao, and Guangyu Dai	
<b>Experimental Study on Normalized Stress-Strain Behavior of Geogrid Reinforced Rubber Sand Mixtures</b> . . . . .	307
Fang-cheng Liu, Meng-tao Wu, and Jun Yang	
<b>Experimental Study of Static Shear Strength of Geomembrane/Geotextile Interface Under High Shear Rate</b> . . . . .	318
Yang Shen, Ji-Yun Chang, Shi-Jin Feng, and Qi-Teng Zheng	
<b>Full-Scale Tests on High Narrowed Mechanically Stabilized Roadbed with Wrapped-Around Geogrid Facing</b> . . . . .	327
Yushan Luo, Chao Xu, and Xiang Wei	
<b>Model Test on the Deformation Behavior of Geogrid Supported by Rigid-Flexible Piles Under Static Load</b> . . . . .	338
Kaifu Liu, Linglong Cao, Yi Hu, and Jiawei Xu	
<b>Numerical and Experimental Investigation of Tensile Behavior of Geogrids with Circular and Square Apertures</b> . . . . .	347
Jie Gu, Mengxi Zhang, and Zhiheng Dai	
<b>Simplified Approach of Seismic Response Simulation of Geosynthetic Reinforced Slope</b> . . . . .	360
Sao-Jeng Chao, Te-Sheng Liu, and Tsan-Hsuan Yu	
<b>Strength Characteristics of Glass Fiber-Reinforced Sand</b> . . . . .	368
Hong Sun, Gang Wu, Chun-yu Song, and Xiu-run Ge	
<b>Three-Dimensional Numerical Analysis of Performance of a Geosynthetic-Reinforced Soil Pier</b> . . . . .	374
Panpan Shen, Jie Han, Jorge G. Zornberg, Burak F. Tanyu, and Dov Leshchinsky	
<b>Numerical Simulation Analysis of Geogrid-Reinforced Embankment on Soft Clay</b> . . . . .	382
Yuanyuan Zhou, Zhenming Shi, Qingzhao Zhang, and Songbo Yu	
<b>Experimental Study on Geocell-Stabilized Unpaved Shoulders</b> . . . . .	390
Jun Guo, Jie Han, Steven D. Schrock, Robert L. Parsons, and Xiaohui Sun	
<b>Model Tests on Performance of Embankment Reinforced with Geocell Under Static and Cyclic Loading</b> . . . . .	399
Zhiheng Dai, Mengxi Zhang, Lei Yang, and Huachao Zhu	

**Comparison Analysis on Behavior of Geosynthetic Reinforcement in Piled Embankments Under Plane Strain and Three-Dimensional Conditions: Numerical Study** . . . . . 411  
 Zhen Zhang, Meng Wang, Guan-Bao Ye, and Jie Han

**Review of Effects of Poor Gripping Systems in Geosynthetic Shear Strength Testing** . . . . . 420  
 Charles Sikwanda, Sanelisiwe Buthelezi, and Denis Kalumba

**Hydraulic Performance of Geosynthetic Clay Liners with Mining Solutions** . . . . . 430  
 Yang Liu, Li Zhen Wang, and Wei Jiang

**Numerical Analysis of Different Effects of GCL and Horizontal Drainage Material on Moisture Field of Highway Subgrade** . . . . . 437  
 Feng Liu, Zhibin Liu, Shujian Zhang, Jian Zheng, Songlin Lei, and Congyi Xu

**DEM Simulation of Pullout Tests of Geogrid-Reinforced Gravelly Sand** . . . . . 446  
 Chao Xu and Cheng Liang

**Large-Scale Model Analysis on Bearing Characteristics of Geocell-Reinforced Earth Retaining Wall Under Cyclic Dynamic Load** . . . . . 455  
 Jia-Quan Wang, Bin Ye, Liang-Liang Zhang, and Liang Li

**Shear Performance of Waste Tires, Geogrid and Geocell Reinforced Soils** . . . . . 463  
 Lihua Li, Feilong Cui, Henglin Xiao, Qiang Ma, and Langling Qin

**Performance of Multi-axial Geogrid-Stabilized Unpaved Shoulders Under Cyclic Loading** . . . . . 473  
 Xiaohui Sun, Jie Han, Steven D. Schrock, Robert L. Parsons, and Jun Guo

**A Comparative Study on Shear Strength of Soil Using Geogrid and Geotextiles** . . . . . 483  
 Akash Chetty, Akhil Jain, Devanshu Mishra, and Kaustav Chatterjee

**Author Index** . . . . . 491



# About the Editors

**Lin Li** received his PhD from University of Wisconsin-Madison, with a focus on Geotechnical Engineering. He has been Geotechnical Laboratory Director in the Department of Civil and Environmental Engineering, Jackson State University since 2005. He is currently a Fellow of American Society of Civil Engineers.

**Bora Cetin** completed his PhD in Geotechnical Engineering at the University of Maryland, College Park. He is currently an Assistant Professor in the Geotechnical and Geoenvironmental Engineering Area in the Department of Civil, Construction, and Environmental Engineering at Iowa State University.

**Xiaoming Yang** completed his PhD in Geotechnical Engineering at the University of Kansas. He is currently an Assistant Professor at Oklahoma State University. He is a Member of American Society of Civil Engineers.



# Monte-Carlo Simulation of Post-construction Settlement After Vacuum Consolidation and Design Criterion Calibration

Wei He<sup>1</sup>(✉), Mathew Sams<sup>1</sup>, Barry Kok<sup>1</sup>, and Pak Rega<sup>2</sup>

<sup>1</sup> Geoinventions Consultancy Services, Brisbane, QLD 4119, Australia

<sup>2</sup> Indonesia Port Corporation, Jakarta Utara, Jakarta 14310, Indonesia

**Abstract.** Reliability-based design is required to minimise risk induced by soil properties variation and laboratory tests discrepancy in geotechnical engineering. A procedure was proposed to analyse probability of post-construction settlement (PCS) after vacuum consolidation, and to calibrate the design criteria to achieve a target reliability index. A Monte-Carlo simulation based on analytical solution of vacuum consolidation was developed to incorporate both primary and secondary consolidation settlement. The reduction of secondary consolidation coefficient during construction was considered in the method. This design and analysis approach were applied in the design review of Kalibaru port, Indonesia. Statistical analysis on soil properties was performed based on comprehensive investigations. The original design was reviewed by using both deterministic analysis with FEM and reliability-based analysis with the proposed method. Lastly, the coefficient of variation (COV) of 1.164 was found for PCS, and design criteria were calibrated to target different levels of  $P_e$ , from 6.7% to 25%.

**Keywords:** Reliability-based geotechnical design · Reclamation  
Post-construction settlement (PCS) · Monte-Carlo simulation

## 1 Introduction

In a geotechnical design, significant uncertainties exist in the process of defining geomaterial properties, which need to be evaluated via reliability analysis. In Kalibaru port, Indonesia, prefabricated vertical drains (PVDs) with preloading and vacuum is proposed to improve the soft ground at a  $900 \times 2600$  m site. Comprehensive investigations were performed to mitigate potential risk. However, there was no similar case using reliability-based design (RBD) could be found in literature. Therefore, a RBD procedure and analysis method need to be developed.

Several reliability-based analysis approaches have been developed for geotechnical structures [1], such as the first-order reliability method (FOSM), the second-order reliability method (SORM), and numerical simulations. Monte-Carlo simulation is a numerical process of repeatedly calculating a performance function, in which the variables within the function are random or contain uncertainty with prescribed probability distributions. A large number of outputs can be obtained and used in statistical analysis for directly estimating the probability of failure ( $P_f$ ), or the

probability of exceedance ( $P_e$ ). In this way, conventional deterministic modelling can be extended to reliability analysis without complex concept and algorithms.

In this paper, RBD procedure based on Monte-Carlo simulation was developed and applied in the Kalibaru port. The mean value of PCS and COV were obtained, then the design criterion was calibrated to achieve reliability index of 1.5. This also provides a detailed case study for future engineering practice.

## 2 Analytical Solution of Vacuum Consolidation Combined with Preloading

PVDs with vacuum and preloading have been widely applied to accelerate the consolidation of soft ground all over the world. The successful applications include Port of Brisbane, Ballina Bypass, and Sunshine Coast Motorway, in Australia [2, 3]; Tianjin Port and Wenzhou Reclamation, in China [4, 5]; Philadelphia International Airport, in USA [6]; North South Expressway, in Malaysia [7]; Second Bangkok International Airport, in Thailand [8]; Shin-Moji Oki Disposal Pond, in Japan [9]. In these projects, fill preloading was combined with vacuum to avoid excessively high embankment and a lengthy preloading period to achieve the same amount of consolidation degree.

A typical cylindrical element of a PVD with preloading and vacuum is shown in Fig. 1. The PVD has the equivalent radius of  $r_w$ , and the influence radius of  $r_e$ . A smear zone with the radius of  $r_s$  is formed during vertical drains installation with a steel mandrel which significantly remoulds its immediate vicinity. Studies showed that, the radius of the smear zone is about 2.5 times the equivalent radius of the mandrel, and the lateral permeability within the smear zone is 61%–92% of the outer undisturbed zone [10]. Preloading,  $p_0$ , is applied on the ground surface, and vacuum pressure,  $p_s$ , is applied via pump connected to PVDs. Experience has shown that the vacuum pressure applied in field through PVDs may decrease with depth. Let the decreasing rate is  $\lambda$ , then the suction propagated to the toe is  $p_s - \lambda l$  when the length of PVDs,  $l$ , is not sufficient to reduce the suction down to zero. This pressure loss rate,  $\lambda$ , was found up to 3 kPa/m in experiments [11].




Fig. 1. Illustration of PVDs with preloading and vacuum pressure [2]

Settlement development by using PVDs with preloading and vacuum incorporates both primary and secondary consolidation.

**Primary consolidation.** The primary consolidation of soil with PVDs is dominated by radial drainage. The theory of radial drainage and consolidation has been developed by many researchers [12, 13]. Consider a thin layer with  $\Delta H$  in thickness, the excess pore pressure during vacuum consolidation can be solved by:

$$\frac{\bar{u}_{h,t}}{u_0} = \left(1 + \frac{p_s}{u_0}\right) e^{\left(\frac{-8c_h t}{\mu d_e^2}\right)} - \frac{p_s}{u_0} \quad (1)$$

where,  $\bar{u}_{h,t}$  is excessive pore pressure at depth of  $h$  and time of  $t$ ;  $u_0$  is the initial excessive pore pressure induced by preloading,  $p_0$ ;  $c_h$  is the coefficient of consolidation;  $d_e$  is the diameter of the influencing zone, and  $d_e = 2r_e$ ;  $\mu$  is a factor as follow:

$$\begin{aligned} \mu = & \frac{n^2}{n^2 - 1} \left[ \ln\left(\frac{n}{s}\right) + \frac{k_h}{k_s} \ln(s) - \frac{3}{4} \right] \\ & + \frac{s^2}{n^2 - 1} \left( 1 - \frac{s^2}{4n^2} \right) + \frac{k_h}{k_s} \frac{1}{n^2 - 1} \left( \frac{s^4 - 1}{4n^2} - s^2 + 1 \right) \end{aligned} \quad (2)$$

where,  $n = r_e/r_w$ ,  $s = r_s/r_w$ .

The degree of consolidation is:

$$U_{h,t} = \frac{1 - \bar{u}_t/u_0}{1 - u_\infty/u_0} = \frac{u_0 - \bar{u}_t}{u_0 - p_s} \quad (3)$$

Thus, primary consolidation can be obtained by:

$$s_t = s_p U_{h,t} \quad (4)$$

where,  $s_p$  is the ultimate primary consolidation computed by,

$$s_p = \frac{C_c}{1 + e_0} \Delta H \log \left( \frac{\sigma'_{z,t}}{\sigma'_{z,0}} \right) \quad (5)$$

where,  $C_c$  is compression index;  $e_0$  is initial void ratio;  $\sigma'_{z,t}$  is vertical effective stress at time  $t$ ;  $\sigma'_{z,0}$  is initial vertical effective stress at time 0.

Except for loading process, the recompression index,  $C_r$ , is smaller than  $C_c$ .

**Secondary consolidation.** Secondary consolidation plays an important role in long-term settlement. If the time to reach the end of primary consolidation is relatively short which benefits from vacuum consolidation and reloading, the time-dependent settlement is basically controlled by the secondary consolidation [14].

Secondary consolidation,  $s_s$ , is given by the formula:

$$s_s = \frac{\Delta H}{1 + e_0} C_\alpha \log\left(\frac{t}{t_{95}}\right) \quad (6)$$

where,  $C_\alpha$  is the coefficient of secondary consolidation;  $t_{95}$  is the time when primary consolidation reaches 95% consolidation degree.

For simplification, the time at the end of construction was taken as  $t_{95}$  in this paper.

A number of authors [15–17] have reported the significant reduction of secondary consolidation when the soil is over-consolidated even to a modest degree. Laboratory and field experiments results indicated a decreasing exponential relationship between over-consolidation ratio (OCR) and  $C_\alpha$ . The uniform expression is [16]:

$$C_\alpha = 10^{(A+B \cdot OCR)} + C \quad (7)$$

where, A, B, and C are fitting parameters, as recommended in papers [14, 16].

Kosaka [17] proposed the formula to determine OCR as follow:

$$OCR = \frac{\sigma'_{z,0} + (\Delta\sigma'_1 + \Delta\sigma'_s) \times U}{\sigma_{z,0} + \Delta\sigma'} \quad (8)$$

where,  $\sigma_{z,0}$  is initial effective stress;  $\Delta\sigma'$  is effective stress induced by design load;  $\Delta\sigma'_1$  is effective stress induced by preloading;  $\Delta\sigma'_s$  is effective stress induced by vacuum pressure;  $U$  is the consolidation degree at the time of preloading and vacuum removal.

### 3 Reliability-Based Analysis and Design Approach

#### 3.1 Monte-Carlo Simulation Based on Analytical Solution

The analytical solution of vacuum consolidation and preloading can be incorporated into reliability procedure by using Monte-Carlo simulation (MCS), as indicated within the dashed box in Fig. 2. Comparing to deterministic analysis, MCS computes PCS repeatedly (usually > 5000 times) based on randomly generated samples of soil parameters, and perform statistical analysis on output to extract its probabilistic characteristics. MCS has been widely used in probabilistic analysis of geotechnical engineering problems, such as slope stability analysis, retaining structures, and foundations [1]. However, no study was found in vacuum consolidation combined with preloading.

For soil consolidation, obvious correlations exist among soil parameters such as  $C_c$ , and  $C_r$ . Thus, these correlations need to be considered in random samples generation.

In this paper, MCS based on the analytical solution was programmed with GNU software, Octave 4.0.




Fig. 2. Flowchart of RBD based on MCS

### 3.2 Reliability-Based Design Approach

Geotechnical design codes have been migrating towards RBD concepts for several decades [18]. The latest International Standard, ISO2394-2015 [19], has differentiated and related three levels of approach: risk-informed decision making, reliability-based design (RBD), and semi-probabilistic approaches. Comparing to semi-probabilistic approaches such as the load and resistance factor design (LRFD) approach in North American [20], and the characteristic values and partial factors used in the limit state design approach in Eurocode 7 [21] and AS 5100.3-2004 [22], RBD is based on a target reliability index that explicitly reflect the uncertainty of the parameters and their correlation structure, thus more suitable for large scale projects.

As shown in Fig. 2, the reliability index,  $\beta$ , need to be checked in RBD rather than overall factor of safety. EN1990-2002 [23] recommends the target reliability index,  $\beta_t$ ,

For PCS,  $\beta_i$  for serviceability (irreversible) limit state in 50 years is 1.5. The Chinese Standard GB 50068-2001 [24] states that,  $\beta_i$  is between 0 to 1.5 for serviceability limit state, depending on the reversibility. The target reliability index of 0 and 1.5 are equivalent to failure probability of 50% and 6.7%, respectively.

In contrast to probability of failure for ultimate limit state, a low probability of exceedance needs to achieve for PCS. The concept of probability of exceedance and design consideration are illustrated in Fig. 3. Assume that settlement conforms reasonably well to a normal or log normal distribution. The probability density function (PDF) 1 has the same mean value  $\mu_1$ , but smaller standard deviation than PDF 2, namely  $\sigma_1 > \sigma_2$ . The area under each PDF in the excessive settlement zone indicates probability of exceedance,  $P_e$ . Although PDF2 has the same mean value, which is usually the criterion in design, its  $P_e$  is obviously higher than that of PDF 1. This indicates that, the same design criterion does not necessarily mean the same level of  $P_e$ .




Fig. 3. The concept of  $P_e$  and design strategy

With the larger variation level (larger standard deviation) such as in PDF 2, the design needs to be offset to solution represented by PDF 3, which has the same standard deviation  $\sigma_2$ , but stringent design criterion (smaller mean value  $\mu_2$ ). Each  $P_e$  can be related to a reliability index,  $\beta$ , as indicated in Fig. 3.

Therefore, the variation of settlement can be considered in design criteria to achieve a specific level of  $P_e$ . When the settlement conforms to log normal distribution, Settlement Ratio (SR) can be applied in design according to the COV of settlement and a target exceedance probability from 6.7% to 25.0%, which is plotted in Fig. 4.

Given the maximum allowable settlement is  $S_{allow}$ , and the COV of settlement is 0.3, if the target  $P_e$  is 6.7%, then  $SR = 1.489$  can be obtained from Fig. 4. This means the design criterion needs to be set at  $S_{allow}/1.489$  to achieve the  $P_e$  of 6.7%, which has a reliability index of 1.5.




Fig. 4. Settlement ratio vs. COV for  $P_e$  of 6.7%–25.0%

## 4 Application in Design Review of the Reclamation of Kalibaru Port

### 4.1 Project Summary

The Kalibaru port development is located in the Jakarta bay, and will be constructed from dredged clay and sand materials, as indicated in Fig. 5. The proposed offshore development includes container terminals (CT2 and CT3), product terminals north of CT2 and CT3 and reserve area. In total, the area being constructed is approximately rectangular with dimensions of 2600 m by 900 m.




Fig. 5. Kalibaru port, Indonesia



The naturally occurring seabed is a soft Holocene clay material varying from 8 m up to 29 m thickness in some areas. This is followed by a stiff Pleistocene clay, and dense cemented sand. The reclamation works will involve placing grab-bucket dredged mud (GDM) and cutter-suction dredged mud (CSD) to RL 1.5 m. The water level is considered to be equal to the water level in the Jakarta Bay, which is RL 0.

Comprehensive geotechnical investigations have been performed prior to the design. The locations of boreholes and CPT tests are indicated in Fig. 5. Samples were then tested in laboratory to obtain soil parameters. In the original design, mean value of each parameter was adopted to assess the PCS. Generally, 90-day vacuum consolidation combined with preloading was proposed by the specialist contractor to target the criterion of 300 mm in 50 years after construction.

Geoinventions Consulting Services (GCS) was engaged by IPC to review the design, and RBD procedure was implemented to calibrate the design criterion of PCS. Deterministic analysis by using FEM was also carried out to consider the influence of construction stage.

## 4.2 Deterministic Results by Using FEM

The construction stage of the large-scale reclamation is complex. Preloading and vacuum pressure have to be applied section by section, due to limited volume of fill and quantity of pumps. The construction of filling for preloading and installation of PVDs are time-consuming which also elongate the construction period. To assess PCS under the real construction process, a 2D finite element software, OptumG2 (version 2017.05.20), was used in the deterministic analysis.

To simplify the modelling process, the analysis for each section starts from the stage when GDM/CSD have been built up to RL 1.5. The sections of wick drains/PVDs are modelled using fixed excess pressure lines. These allow the excess pore pressure to be fixed to any value. Pressure loss of 3 kPa/m was considered and average vacuum pressure was applied along the fixed excess pressure lines. Main soil parameters adopted in the FEM analysis are listed in Table 1. The secondary consolidation coefficient,  $C_{\alpha}$ , was not tested in the investigations. The test results performed at the Belawan Port which is approximately 200 km away from the site were used [25].

**Table 1.** Parameters adopted in Section 3-N analysis

Parameter	Upper Holocene Clay	Lower Holocene Clay	Stiff Clay	GDM/CDM
$\gamma$ (kN/m <sup>3</sup> )	14.3	14.6	15.8	12.0
$C_c$	0.96	0.85	0.59	1.08
$C_r$	0.148	0.108	0.046	0.18
$C_v$ (m <sup>2</sup> /year)	1.33	1.37	4.43	3.50
$C_{\alpha}$	0.036	0.036	–	0.036
$e_0$	3.00	2.54	1.68	3.50
OCR	1.00	1.00	2.50	1.00




Fig. 6. Settlement development by FEM

A total of six cross sections have been considered across the project – Sections. 2-S, 2-N, 3-S, 3-N, 6-S, and 9-S. These sections are shown in Fig. 1. The settlement results for all six sections is illustrated in Fig. 6. These results indicate that the maximum total settlement occurs for Section 3-S, with a result of 10.4 m. Figure 6 also indicates that Section 2-N and 3-N exhibit very similar settlement profiles. Sections 6-S and 9-S are also similar, but exhibit a 1 m difference in total settlement due to varying soil profile and different construction process. All sections show a similar gradient to the secondary settlement line (after approx. 1000 days), except for Section 3-S which has almost doubled the thickness of soft clay.

### 4.3 Reliability-Based Design Calibration

According to the FEM analysis results, the soft soil and GDM/CDM are most critical for settlement analysis. GDM/CDM is the dredged layer which can be considered reasonably uniform. Thus, the thick soft soil layer dominates the variation of PCS. Statistical analysis was implemented on soft soil based on gathered test results from the principal geotechnical designer, LAPI. Log normal distribution function was adopted to fit each parameter. Six parameters: unit weight; compression index,  $C_c$ ; recompression index,  $C_r$ ; Coefficient of consolidation,  $C_v$ ; secondary consolidation coefficient,  $C_\alpha$ , and

Table 2. Mean Values and Variation of Parameters

Parameter	Mean Value	Standard Deviation	Range
$\gamma$ (kN/m <sup>3</sup> )	14.949	2.516	12.26–19.60
$C_c$	0.883	0.324	0.110–2.080
$C_r$	0.124	0.012	0.030–0.300
$C_v$ (m <sup>2</sup> /year)	4.068	1.666	0.370–4.248
$C_\alpha$	0.037	0.003	0.001–0.499
$e_0$	2.574	2.515	0.040–3.780

initial void ratio,  $e_0$ , are considered in MCS. OCR in Table 1 was ignored in RBD because of its estimation in tests were rough thus less meaningful to taken into account.

Correlations exist among parameters listed in Table 2. The most important correlation is between  $C_c$  and  $C_r$ . Test results shows that the ratio of  $C_c/C_r$  is in a range of 2.81–27.60, which can be fitted by log normal PDF with log normal parameters  $\mu_{LN} = 2.042$ ,  $\sigma_{LN} = 0.629$ , and it is in a range of 3–27. In order to obtain the correlated parameters  $C_c$  and  $C_r$ ,  $C_c$  was generated randomly first with parameters listed in Table 3, then the ratio of  $C_c/C_r$  was generated and  $C_r$  was obtained by  $C_c$  and the ratio. The generated samples and test data were shown in Fig. 7. The generated samples conform to the range of test data.




Fig. 7. Random generation of correlated parameters in MCS




Fig. 8. Repeatedly settlement calculation in MCS

Figure 8 illustrated 10,000 times calculated settlement procession results. The settlement during vacuum and preloading is between 4–23 m depending on parameters generated in MCS. This is a reasonable result with a mean settlement close to FEM result. The settlement development shows different patterns due to combination of parameters.

In total, 10,000 PCS can be obtained in MCS. The absolute value of the output was statistically analysed with log normal PDF, and the result is shown by histogram in Fig. 9. The mean PCS is 917 mm, and the coefficient of variation is 1.164. This indicated a large variation exists because of the variation of soil properties. According to Fig. 4, the settlement ratio is 2.6, 2.1, 1.7, 1.4, 1.2 when target  $P_e$  is 6.7%, 10%, 15%, 20%, 25%, respectively. Taking the target  $P_e$  is 20%, GCS sets the design criterion at  $300 \text{ mm}/1.4 = 214 \text{ mm}$ .




Fig. 9. Probabilistic analysis of MCS outputs

## 5 Conclusions

A reliability-based geotechnical design procedure with analysis approach was proposed in this paper. And this method was applied in the design review of Kalibaru port, Indonesia. Based on the practice, conclusions can be drawn as follow:

- (1) A design criterion requires to be calibrated by using reliability-based design method in large scale projects to mitigate potential risk. This guarantees that a target probability of exceedance can be achieved for PCS in design;
- (2) The settlement ratio diagram was developed to determine a settlement criterion based on the COV of PCS and a target exceedance probability, which is straightforward in the design process;
- (3) The Monte-Carlo simulation based on analytical solution of vacuum consolidation and preloading was coded and incorporated in the RBD of Kalibaru port.

The COV was found to be 1.164, and the settlement ratios were recommended to target exceedance probabilities of 6.7%–25%. This RBD strategy can take into account the uncertainty induced by soil properties variation, and provide a reasonable criterion for engineering purpose.

## References

1. Phoon, K.K., Ching, J.: Risk and Reliability in Geotechnical Engineering. CRC Press (2014)
2. Indraratna, B., Rujikiatamjorn, C., Geng, X.: Performance and prediction of surcharge and vacuum consolidation via prefabricated vertical drains with special reference to highways, railways and ports. In: International Symposium on Ground Improvement, 31 May–1 June 2012, Brussels, Belgium, pp. 145–168 (2012)
3. Indraratna, B., Kan, M.E., Potts, D., Rujikiatkamjorn, C., Sloan, S.W.: Analytical solution and numerical simulation of vacuum consolidation by vertical drains beneath circular embankments. *Comput. Geotech.* **80**, 83–96 (2016)
4. Chu, J., Yan, S.W., Yang, H.: Soil improvement by the vacuum preloading method for an oil storage station. *Geotechnique* **50**(6), 625–632 (2000)
5. Tang, T.Z., Dong, J.P., Huang, J.Q., Zhang, X.Z., Guan, Y.F.: Experimental research on hydraulic filled mud consolidated by vacuum preloading method combining long and short boards with thin sand cushions. *Chin. J. Geotech. Eng.* **34**(5), 899–905 (2012)
6. Holtan, G.W.: Vacuum stabilization of subsoil beneath runway extension at Philadelphia international airport. In: Proceedings of 6th ICSMFE, vol. 2 (1965)
7. Yee, K., Ooi, T.A.: Ground improvement – a green technology towards a sustainable housing, infrastructure and utilities developments in Malaysia. *Geotech. Eng. J. SEAGS & AGSSEA* **4**(3), 1–20 (2010)
8. Seah, T.H.: Design and construction of ground improvement works at Suvarnabhumi airport. *Geotech. Eng. J. SE Asian Geotech. Soc.* **37**, 171–188 (2006)
9. Ikeda, H., Kawano, M., Kiyoyama, T.: Performance and prediction of dredged clay reclaimed land by vacuum consolidation method. *Int. J. GEOMATE Geotech. Constr. Mater. Environ.* **8**(1), 1300–1307 (2015)
10. Indraratna, B.: Recent advances in the application of vertical drains and vacuum preloading in soft soil stabilisation. *Aust. Geomech. J.* **45**(2), 1–53 (2010)
11. Liqiang, S.: Theory and model test study of recently reclaimed soil foundation. Ph.D thesis, Tianjin University (2010)
12. Hansbo, S.: Consolidation of fine-grained soils by prefabricated drains. In: Proceedings of 10th International Conference SMFE, vol. 3, Stockholm, Sweden, pp. 677–682 (1981)
13. Indraratna, B., Sathanathan, I., Rujikiatkamjorn, C., Balasubramaniam, A.S.: Analytical and numerical modeling of soft soil stabilized by prefabricated vertical drains incorporating vacuum preloading. *Int. J. Geomech.* **5**(2), 114–124 (2005)
14. Alonso, E.E.: Precompression design for secondary settlement reduction. *Géotechnique* **51**(51), 822–826 (2001)
15. Mesri, G.: Coefficient of secondary compression. *J. Soil Mech. Found. Div. ASCE* **99**(1), 77–91 (1973)
16. Fukazawa, E., Yamada, K., Kurihashi, H.: Predicting long-term settlement of highly organic soil ground improved by preloading. *J. Geotech. Eng. JSCE* **493**(3–27), 59–68 (1994)
17. Kosaka, T., Hayashi, H., Kawaida, M., Teerachaikulpanich, N.: Performance of vacuum consolidation for reducing a long-term settlement. *Japan. Geotech. Soc. Spec. Publ.* **2**(59), 2015–2020 (2016)

18. Fenton, G.A., Naghibi, F.: Reliability-based geotechnical design code development. *Vulnerability, Uncertainty, Risk ASCE*, 2468–2477 (2014)
19. International Organization for Standardization. *General principles on reliability of structures*. ISO2394: 2015, Geneva, Switzerland (2015)
20. Federal Highway Administration (FHWA). *Load and Resistance Factor Design (LRFD) for highway bridge substructures*. Publication No. FHWA-HI-98-032 (2001)
21. European Committee for Standardization (CEN). *Eurocode 7: geotechnical design — part 1: general rules*. EN 1997–1:2004, Brussels, Belgium (2004)
22. AS 5100.3-2004. *Bridge Design, Part 3: Foundations and Soil-Supporting Structures* (2004)
23. European Committee for Standardization (CEN). *Eurocode — basis of structural design*. EN 1990:2002, Brussels, Belgium (2002)
24. GB 50068-2001. *Unified Standard for Reliability Design of Building Structures*, Beijing (2001)
25. Toha, F.X.: Secondary compression of belawan clay. In: *International Symposium on Soft Soils in Construction and Deep Foundations*, IGEA - JSSMFE, Jakarta (1987)